

Ve Connect the World






POE-12/2.5

IEEE 802.3af Power over Ethernet, 48V Power Injector and Splitter (12V, 2.5Ø/5.5Ø)

PheeNet POE-12/2.5 is an IEEE 802.3af Power over Ethernet with 48V Power Injector and Splitter (12V, 2.1Ø/5.5Ø), which is a innovative technology for powering Ethernet devices such as IP telephone, Web Camera and Wireless AP. POE-12/2.5 can transform AC power to 48V DC power and inject 48V DC through CAT-5 cable pin# 4, 5, 7 and 8 into remote devices; therefore, user can apply POE-12/2.5 to convey the power and data to your LAN equipment through Ethernet cable, which extends the reach of your Web Camera, VoIP and wireless AP more efficiently. Moreover, secure features like Short Circuit Protection, Over Load Protection and High Voltage Protection prevent Ethernet devices from circuit shortage resulted from wrong pin installation or cable damage.

APPLICATION



Features

The maximum distance of RJ-45 Cable between Power Injector and Splitter is 100m **DC Injector Features:**

- ◆Transform AC power to 48V DC power. Inject 48V DC through CAT-5 cable pin# 4,5, 7, 8, into remote devices such as Wireless AP, IP Phone, Web Camera, etc
- Protection: Short Circuit Protection: Any output short GND terminal will lead Auto-Reset. Over Load Protection: Load Current over 395mA will lead Auto-Reset. High Voltage
 Protection: Output DC voltage over 57V will lead

Splitter Features:

- Work with Power Injector, as a data/power splitter and DC to DC converter
- SHORT CIRCUIT PROTECTION: Any output Short GND Terminal will not damage the Power Supply and will.Auto-Reset.

Specification

| Industrial Standard: | |
|----------------------|------------------------------------|
| Standard | Compliant with IEEE 802.3af |
| DC Injector | Input : 100V ~240V AC, |
| | output :48V DC (Max. 350mA) |
| Splitter | Input: 48VDC, 300mA |
| | Output: 12VDC, 1.0A |
| Category 5 Pin Usage | Data: 1, 2, 3, 6 |
| | Power: 4, 5, 7, 8 |
| Hardware: | |
| CAT-5 UTP Cable | 200mm |
| Length(splitter) | |
| DC Power Cable | 200mm |
| Length(splitter) | |
| Power Jack | Diameter: 2.5Ф/ 5.5Ф |
| | length: 12±0.5mm |
| | 180 degree angle |
| | Polarity : inside (+), outside (-) |
| Dimensions | Injector: 85(L) x 76(W) x 36(H)mm |
| | Splitter: 85(L) x 76(W) x 36(H)mm |
| Splitter Weight | 135g |
| Environment | Temperature operating: 0°C to 60°C |
| | Temperature storage: -10°C to 70°C |
| Humidity | 5°%~90% |
| Certificate | FCC,CE |

PheeNet Technology Corp.

Rm. 3, 20F, NO. 79, Hsin Tai Wu Rd., Sec. 1, Hsi-Chih, Taipei, Taiwan http://www.pheenet.com TEL:886-2-26982011 FAX:886-2-26981421 PheeNe



